

Theatre Technical Specifications

April 2018

Technical Coordinators: Liam Mitchinson and Trevor Ploeg

Phone number:(03) 9754 8723Fax number:(03) 9754 8523Email address:tech@burrinja.org.au

Venue Manager: Toni Kirk

Phone number: (03) 9754 8723 Fax number (03) 9754 8523 Email: tonik@burrinja.org.au

Venue Details:

351 Glenfern Road, Upwey, 3158Phone number:(03) 9754 8723Fax number(03) 9754 8523:Website:www.burrinja.org.auMelways ref:75 B12

STAGE

Brief Stage Description:

Un-raked, un-raised, without a proscenium arch. The floor is sprung with a black finish. Hanging facilities are by Tri Truss on dollies. There is a crossover behind stage wall (cyc) with access to dressing rooms.

Stage rake	NONE
Stage Dimensions: Proscenium	
Width	14 m with legs out.
Width	9.4 m with legs in (adjustable)
Height	7.5 m from stage floor to bottom of Catwalk.
Setting Line	

The SL is 9.3 metres from the cyclorama wall.

D	istance From (SL = Setting Line, CL = C	entre Line)
	SL to DS edge of apron	2 m * (further extension possible by arrangement)
	SL to rear wall	9.3 m*
	CL to OP wall (or obstruction)	7 m
	CL to PS wall (or obstruction)	7 m
	Stage to underside of catwalk	7.5

*Please note that the stage apron is a flat floor to the seating bank, so the front edge of the playing space can be set anywhere in front of there. There are 2 removable rows of seating (AA & BB) that can be placed on this flat area. The Setting Line mentioned here is the most forward position that the front of house curtain can be placed.

Additional Staging:

Transtage Premiere staging units

Dimensions	1m x 1m x 400mm
Treads available	Yes, 2 sets
Skirts available	Yes, 8 x 2m skirts
Surface	Duraflex hard textured surface, black
Load limit	950kg/m ²
Quanitity	A maximum of 20 staging units are available for a free standing stage of 20m ² .
Hand rails	N/A

Auditorium:

Upper and Lower level seating with removable balcony options.

Seating capacity	300 (400 on appro	val by management)
Seating capacity w	ith vormitory out	Max: 384
Seating capacity w	ith extended apron	Max: 364
Seating capacity <u>w</u> Orchestra lift/pit se		No Orchestra lift/pit

Flying Facilities: No Flying system

Rigging Facilities:

Rigging System

3 full stage lengths of Tri truss on dollies that run up and down stage are fully riggable. These bars are <u>not</u> able to be flown in to stage level. The lower chord height is fixed at 9.2m above stage level. They are able to be positioned anywhere between the upstage wall and Setting Line.

3 catwalks with adjoining tech balconies used for LX rigging and possible Hanging Points

LX bars cannot be swung

Drapery:

*Туре	Material	Colour	Width	Height	Quantity
House Curtain	Wool	Black		9.2	2
Legs	Wool	Black	2.3	7.3	10
Blacks	Molten	Black	3	9.2	6

House Curtain is operated by manual pulley system PS

Legs are able to slide up and down stage on tracks as well as swing on and off stage. (they are not removable)

Blacks are hung with Velcro tabs from the Tri Truss on dollies.

Access Equipment:

No Elevated Work Platform

All rigging from Catwalks Lighting Bridge, Tech Balconies and Balcony.

Loading Dock:

Access

Truck access from Matson Drive with direct access to staging area.

Loading Dock Height	Loading dock has a leveller platform with maximum truck height clearance of 3.9 m
Door Dimensions	2.8 m High
	1.9 m Wide

Restrictions / Obstructions

For Bump-ins, loading bay can only be used on weekdays from 7:00am and weekends from 9:00am until 1 hour prior to performance. Bump-outs must be completed by 1:00am.

Access is restricted to one truck at a time.

Staging Notes:

All flown items must be rigged with rated equipment and is subject to approval by a venue representative

Scenery, backdrops and any other material must **not** be attached or placed against the rear stage cyc wall in any manner.

LIGHTING

House Lights: Independant control	YES
Control positions	Control Desk and DS PS and DS OP
Fade time adjustable	No. Has variable dimming -100%; 65%; 35%; 10%
Positions:	
Stage LX Bars	Fixed multiple uni-strut from catwalks and lighting bridge
	See LX dimesnions plan for LX bar locations
FOH Lighting Bridge 1 (Setting Line to lighting	
Usable bar width	14 m
Notes	This point consists of 2 bars with one sitting approx. 60 cm above the lower.
Catwalk 1 down stage s	ide (LX1a)
Setting Line to lighting	bar Lower Bar is 7.7 m at 12 degrees
Usable bar width	14 m
Notes	This point consists of 2 bars with one sitting approx. 60 cm above the lower.

Setting Line to lighting bar	Lower Bar is 7.5 m at 1.5 degrees
Usable bar width	14 m
Notes	This point consists of 2 bars with one sitting approx. 60 cm above the lower.

Catwalk 2 down stage side (LX2)

Setting Line to lighting bar	Lower Bar is 8.9 m at 32 degrees
Usable bar width	14 m
Notes	This point consists of 2 bars with one sitting approx. 60 cm above the lower.

Catwalk 2 up stage side (LX 3)

Setting Line to lighting bar	Lower Bar is 9.8 m at 40 degrees
Usable bar width	13.5 m
Notes	This point consists of 2 bars with one sitting approx. 60 cm above the lower.

Tech Balcony Bar PS & OP

Centre Line to lighting bar Notes

10.6 m at 41 degrees

FOH Boom (PS & OP)

Setting Line to FOH Perch **12.1 m at 42 degrees** Distances are to the highest downstage point of boom or perch.

2 x 3 metre push up stands

2 x 3 metre push up stands available for side stage lamp hanging.

Control:

Lighting desk	LSC Maxim XXL
Control channels	120 (no pat pad)
Signal distribution	2 DMX universe streams available.

Dimmer Racks:

2 X EKO 24 dimmer Channels

4 X Solution Cool 12 Dimmer Channels

Total Dimmer Channels	96

Dimmer Locations Tech Balcony PS

Stage Luminare:

Profiles

Make	Model	Angle	Detail / Accessories	Watt	Total
SPX	SPX15-35	35 deg	colour frame and shutters and B size gobo holders	800W	28
SPX	SPX25-50	50 deg	colour frame and shutters and B size gobo holders	800w	16

Fresnel's

Make	Model	Detail / Accessories	Watt	Total
Rama	16RAFR175PL	colour frame barn doors	1200W	24
Selecon	12ACFPL	colour frame barn doors	650W	6

PC

Make	Model	Detail / Accessories	Watt	Total
Selecon		colour frame	1200W	6

LED Par Cans

Make	Model	Detail / Accessories	Watt	Total
Showtec	Club Par 12-6 RGBWAUV	DMX control	12 x 8w	9
ProShop	Tri 18 RGB	DMX control	18 x 3w	4

Cyc Battens

Make	Model	Detail / Accessories	Watt	Total
LUI	0LUICYC3PL	3-way Cyc Batten	1000W	6

Additional Lighting:

Item	Make	Model	Detail / Accessories	Watt	Total
Mirror Ball			With Motor		1

Power: 3 Phase Outlets 2 D.S.OP 2 D.S.P 1 US OP 1 US P

Cabling:

240v Extension Cable

The Theatre has a good stock of extension leads to accommodate standard use and needs.

Looms

None

3 phase Extensions

None

<u>AUDIO</u>

Control Positions:

Control Desk

Rear centre of stalls open space dedicated position.

Control:

Primary Mixer

Allen Heath 24 channel 4 stereo outputs 6 aux sends phantom power.

EQ

dbx 2231 for FOH Yamaha Q2031 for Monitors

FX

Yamaha SPX2000

Compression / Limiter / Gate

dbx 166XL

FOH Speakers

3 x JBL VRX 932 LAP Line Arrays (flown) – per side 1 x JBL VRX 918 SP Sub (flown)– per side

Audio Monitors

- 2 x 2000 w QSC K12.2 powered speakers
- 2 x 500 w Soundking powered speakers
- 2 x 250 w Soundking powered speakers

Cabling: Audio Cable

The Theatre has good stock for standard venue use.

Multicore

1 X 20m Multicore 12 sends 4 returns

Microphones:

Make	Model	Detail / Accessories	Use	Total
Shure	SM 58		Vocals	6
Audio Technica	ATM450		Instrument	6
Shure	MX412S/S	Lectern Microphone	Vocals	1
Sennheiser	ME2	Clip on Lapel	Vocals	2
Sennheiser	100-835-G3	Hand held Wireless	Vocals	2

D.I.s

2 X Leem NDR DI

1 X Behringer Ultra DI

Line Patching:

Location	Quantity	Detail
Downstage P	8	6 sends, 2 returns
Downstage OP	8	6 sends, 2 returns
Downstage P stage floor trap	8	6 sends, 2 returns
Downstage OP stage floor trap	8	6 sends, 2 returns
Upstage P stage floor trap	4	3 sends, 1 return
Upstage OP stage floor trap	4	3 sends, 1 return
Rehearsal Position	4	3 sends, 1 return
Catwalks	15	10 Sends, 5 returns
Balcony P	4	3 sends, 1 return
Balcony OP	4	3 sends, 1 return

AUDIO VISUAL

Projectors:

Туре	Model	Detail	Total
Sanyo Projector	PLC-XP200L	VGA or SDI (RCA converter) signal in	1
Sanyo short throw lens	W31		1

Screens:

Projection Screen

Theatre Cyclorama is used as main screen.

Screen dimensions 10 m wide X 7.5 m high

Portable screen available on request 1.8m X 1.4

Projector Rigging Points:

Permanently rigged centre down stage off Catwalk 1 (down stage of curtain track) Controlled by wired remote at control desk

BACKSTAGE

Communications:

Stage Managers Desk

The Stage Managers desk is in Prompt corner. It is fitted with CCTV monitoring, Talkback to Control Desk and Dressing/Green Rooms and Paging to Foyer.

Dressing Rooms:

Dressing Room	Capacity	Toilets	Shower	Details
Principal 1	4	M/F	YES	Principal.1 and Principal.2 can be
Principal 2	4	M/F	YES	joined or divided as needed
Dressing room 3	30	M/F	YES	D.R.1 and D.R.2 can be joined or
Dressing room 4	35	M/F	YES	divided as needed
Dressing room 5	10	M/F	YES	Upstairs next to Black Box Space
Black Box	100	No	No	This Space can be used for large
				groups by arrangement

All dressing rooms and Green Rooms have CCTV and Audio stage relay

Stage Door:

Access

Stage door is next to loading dock on Matson Drive. Access needs to be controlled by personnel.

VENUE:

Venue Address	351 Glenfern Road Upwey 3158 (Enter from Matson Drive)
Venue Postal Address	351 Glenfern Road Upwey 3158

Staff Contacts:

Venue Tech Co-ordinators Liam Mitchinson and Trevor Ploeg

Email Address Phone Number tech@burrinja.org.au (03) 9754 8723

Venue Manager

Email Address Phone Number

Toni Kirk tonik@burrinja.org.au (03) 9754 8723

Box Office

Anda Petrapsch

Email Address Phone Number boxoffice@burrinja.org.au (03) 9754 8723