

Theatre Technical Specifications

April 2025

Technical Coordinator: Trevor Ploeg

Phone number: (03) 9754 8723

Email address: tech@burrinja.org.au

Venue and Experience Manager: Sally Young

Phone number: (03) 9754 1509 Email: venue@burrinja.org.au

Venue Details:

351 Glenfern Road, Upwey, 3158
Phone number: (03) 9754 8723
Website: www.burrinja.org.au

STAGE

Brief Stage Description:

Un-raked, un-raised, without a proscenium arch. The floor is sprung with a black finish. Hanging facilities are by Tri Truss on dollies. There is a crossover behind stage wall (cyc) with access to dressing rooms.

Stage rake NONE

Stage Dimensions:

Proscenium

Width 14 m with legs out.

Width 9.4 m with legs in (adjustable)

Height 7.5 m from stage floor to bottom of Catwalk.

Setting Line

The SL is 9.3 metres from the cyclorama wall.

Distance From (*SL* = Setting Line, *CL* = Centre Line)

SL to DS edge of apron **2 m*** (further extension possible by arrangement)

SL to rear wall 9.3 m*
CL to OP wall (or obstruction) 7 m

CL to PS wall (or obstruction) 7 m

Stage to underside of catwalk 7.5

Additional Staging:

Transtage Premiere staging units

Dimensions 1m x 1m x 400mm

Treads available Yes, 2 sets

Skirts available Yes, **8 x 2m skirts**

Surface Duraflex hard textured surface, black

Load limit 950kg/m²

Quantity A maximum of **20 staging units are available** for a

free standing stage of 20m².

Hand rails N/A

^{*}Please note that the stage apron is a flat floor to the seating bank, so the front edge of the playing space can be set anywhere in front of there. There are 2 removable rows of seating (AA & BB) that can be placed on this flat area. The Setting Line mentioned here is the most forward position that the front of house curtain can be placed.

Auditorium:

Upper and Lower level seating with removable balcony options.

Seating capacity 388 plus 12 with restricted views

Seating capacity with vormitory out Max: 384

Seating capacity with extended apron Max: 364

Seating capacity without

Orchestra lift/pit seating installed No Orchestra lift/pit

Flying Facilities:

No Flying system

Rigging Facilities:

Rigging System

3 full stage lengths of Tri truss on dollies that run up and down stage are fully riggable. These bars are <u>not</u> able to be flown in to stage level. The lower chord height is fixed at 9.2m above stage level. They are able to be positioned anywhere between the upstage wall and Setting Line.

3 catwalks with adjoining tech balconies used for LX rigging and possible Hanging Points

LX bars cannot be swung

Drapery:

*Type	Material	Colour	Width	Height	Quantity
House Curtain	Wool	Black		9.2	2
Legs	Wool	Black	2.3	7.3	10
Rear Curtain	Wool	Black		9.2	2

House Curtain is operated by manual pulley system PS

Legs are able to slide up and down stage on tracks as well as swing on and off stage. (they are not removable)

Rear Curtain is operated by manual pulley system PS

Access Equipment:

No Elevated Work Platform

All rigging from Catwalks Lighting Bridge, Tech Balconies and Balcony.

Loading Dock:

Access

Truck access from Matson Drive with direct access to staging area.

Loading Dock Height Loading dock has a leveller platform with maximum truck

height clearance of 3.9 m

Door Dimensions 2.8 m High

1.9 m Wide

Restrictions / Obstructions

For Bump-ins, loading bay can only be used on weekdays from 7:00am and weekends from 9:00am until 1 hour prior to performance.

Bump-outs must be completed by 1:00am.

Access is restricted to one truck at a time.

Staging Notes:

All flown items must be rigged with rated equipment and is subject to approval by a venue representative.

Scenery, backdrops, and any other material must **not** be attached or placed against the rear stage cyc wall in any manner.

LIGHTING

House Lights:

Independent control YES

Control positions Control Desk and DS PS and DS OP

Fade time adjustable No. Has variable dimming -100%; 65%; 35%; 10%

Positions:

Stage LX Bars Fixed multiple uni-strut from catwalks and lighting bridge

See LX dimensions plan for LX bar locations

FOH Lighting Bridge 1 (FOH 2)

Setting Line to lighting bar Lower Bar is 9.4 m at 37 degrees

Usable bar width 14 m

Notes This point consists of 2 bars with one sitting approx. 60 cm

above the lower.

Catwalk 1 down stage side (FOH 1)

Setting Line to lighting bar Lower Bar is 7.7 m at 12 degrees

Usable bar width 14 m

Notes This point consists of 2 bars with one sitting approx. 60 cm

above the lower.

Catwalk 1 up stage side (LX1)

Setting Line to lighting bar Lower Bar is 7.5 m at 1.5 degrees

Usable bar width 14 m

Notes This point consists of 2 bars with one sitting approx. 60 cm

above the lower.

Catwalk 2 down stage side (LX2)

Setting Line to lighting bar Lower Bar is 8.9 m at 32 degrees

Usable bar width 14 m

Notes This point consists of 2 bars with one sitting approx. 60 cm

above the lower.

Catwalk 2 up stage side (LX 3)

Setting Line to lighting bar Lower Bar is 9.8 m at 40 degrees

Usable bar width 13.5 m

Notes This point consists of 2 bars with one sitting approx. 60 cm

above the lower.

Tech Balcony Bar PS & OP

Centre Line to lighting bar 10.6 m at 41 degrees

Notes

FOH Boom (PS & OP)

Setting Line to FOH Perch 12.1 m at 42 degrees
Distances are to the highest downstage point of boom or perch.

2 x 3 metre push up stands

2 x 3 metre push up stands available for side stage lamp

hanging.

Control:

Lighting desk LSC Maxim XXL Control channels 120 (no pat pad)

Signal distribution 2 DMX universe streams available.

Dimmer Racks:

2 X EKO 24 dimmer Channels

4 X Solution Cool 12 Dimmer Channels

Total Dimmer Channels 96

Dimmer Locations Tech Balcony PS

Stage Luminare:

Profiles

Make	Model	Angle Detail / Accessories		Watt	Total
SPX	SPX15-35	35 deg	colour frame and shutters and B size gobo holders	800W	28
SPX	SPX25-50	50 deg	colour frame and shutters and B size gobo holders	800w	16

Fresnel's

Make	Model	Detail / Accessories	Watt	Total
Rama	16RAFR175PL	colour frame barn doors	1200W	24
Selecon	12ACFPL	colour frame barn doors	650W	6

PC

Make	Model	Detail / Accessories	Watt	Total
Selecon		colour frame	1200W	6

LED Par Cans

Make	Model	Detail / Accessories	Watt	Total
Showtec	Fusion PAR Q RGBW	DMX Control	12x 10w	6
Showtech	Club Par 12-6 RGBWAUV	DMX control	12 x 8w	4
ProShop	Tri 18 RGB	DMX control	18 x 3w	3

Cyc Battens

Make	Model	Detail / Accessories	Watt	Total
	CYC 2	Quad RGBAL LED	180W	2

Additional Lighting:

Item	Make	Model	Detail / Accessories	Watt	Total
Mirror Ball			With Motor		1

Power:

3 Phase Outlets

2 D.S.OP

2 D.S.P

1 US OP

1 US P

Cabling:

240v Extension Cable

The Theatre has a good stock of extension leads to accommodate standard use and needs.

Looms

None

3 phase Extensions

None

<u>AUDIO</u>

Control Positions:

Control Desk

Fixed, rear stalls, standard centre position at top of raked seating tiers

Control:

Primary Mixer

Allen & Heath SQ5 48 channel, 16 in, 12 out, 3 St, USB, Multitrack Capable, W/ Dante Card

Expansion

Allen & Heath DT168, 16 in, 8 out, Dante Digital Snake

FOH Speakers

3 x JBL VRX 932 LAP Line Arrays (flown) – per side 1 x JBL VRX 918 SP Sub (flown) – per side

Audio Monitors

8 x 2000 w QSC K12.2 powered speakers

Cabling:

Audio Cable

The Theatre has good stock for standard venue use.

Multicore

1 X 20m Multicore 12 sends 4 returns

Microphones:

Make	Model	Detail / Accessories	Use	Total
Shure	SM 58		Vocals	6
Audio Technica	ATM450	Condenser side entry	Instrument	6
Shure	MX412S/S	Lectern Microphone	Vocals	1
Sennheiser	ME2	Clip on Lapel	Vocals	1
Sennheiser	EW-DX 835-S	Hand held Wireless	Vocals	2
Sennheiser	E816 S	Hand held with switch	Vocal	1

D.I.s

- 1 x Radial ProDI (mono passive)
- 1 x Radial ProD2 (stereo passive)
- 2 X Leem NDR DI (mono passive)
- 1 X Behringer Ultra DI (active)

Line Patching:

Location	Quantity	Detail
Downstage P	8	6 sends, 2 returns
Downstage OP	8	6 sends, 2 returns
Downstage P stage floor trap	8	6 sends, 2 returns
Downstage OP stage floor trap	8	6 sends, 2 returns
Upstage P stage floor trap	4	3 sends, 1 return
Upstage OP stage floor trap	4	3 sends, 1 return
Rehearsal Position	4	3 sends, 1 return
Catwalks	15	10 Sends, 5 returns
Balcony P	4	3 sends, 1 return
Balcony OP	4	3 sends, 1 return

AUDIO VISUAL

Projectors:

Туре	Model	Detail	Total
Epson Projector	EB-PU2216B	SDI in via a Decimator HDMI to SDI	1
Lens	ELPLW08 Wide Throw Lens		1

Screens:

Projection Screen

Theatre Cyclorama is used as main screen.

Screen dimensions 12 m wide X 7.5 m high

Portable screen available on request 1.8m X 1.4

Projector Rigging Points:

Permanently rigged centre down stage off Catwalk 1 (down stage of curtain track) Controlled by wireless remote at control desk

BACKSTAGE

Communications:

Stage Managers Desk

The Stage Managers desk is in Prompt corner. It is fitted with CCTV monitoring, Talkback to Control Desk and Dressing/Green Rooms and Paging to Foyer.

Dressing Rooms:

Dressing Room	Capacity	Toilets	Shower	Details
Principal 1	4	M/F	YES	Principal.1 and Principal.2 can be
Principal 2	4	M/F	YES	joined or divided as needed
Dressing room 3	30	M/F	YES	D.R.1 and D.R.2 can be joined or
Dressing room 4	35	M/F	YES	divided as needed
Dressing room 5	10	M/F	YES	Upstairs next to Black Box Space
Black Box	100	No	No	This Space can be used for large groups by arrangement

All dressing rooms and Green Rooms have CCTV and Audio stage relay

Stage Door:

Access

Stage door is next to loading dock on Matson Drive. Access needs to be controlled by personnel.

VENUE:

Venue Address 351 Glenfern Road Upwey 3158 (Enter from Matson Drive)

Venue Postal Address 351 Glenfern Road Upwey 3158

Staff Contacts:

Venue Tech Trevor Ploeg

Email Address tech@burrinja.org.au

Phone Number (03) 9754 8723

Venue Manager Nada Čordašić

Email Address venue@burrinja.org.au

Phone Number (03) 9754 1509

Box Office

Email Address hello@burrinja.org.au

Phone Number (03) 9754 8723